

Technical Data Sheet

Textiles & Films | Nylon Fabric | FB458, FB769, FB770

Property	Specification	Test Method
Item No.	FB458, FB769, FB770	
Description	Maritex, 420D Nylon Oxford	
Denier Size	420D x 420D	
Thread Count	50 x 50	
Weight	175 gm/m ²	
Coating	Polyurethane	
Finish	W/R + W/P	
Width	59/60"	
Surface Abrasion (H-18 wheels, 1000g load)	Average No. cycles passed 317 cycles	ASTM D3884-80 (Taber)
Breaking Strength (1BF)	Warp 459.7 Fill 342.0	ASTM D5034-90 (Grab)
Tearing Strength (1BF)	Warp 30.5 Fill 20.4	ASTM D2262-81
Colorfastness to water	Shade change: 5 Staining: 5	ASTM D 3597-89 SEC 7.6
Colorfastness to solvent	Shade change: 5 Staining: 5	ASTM D 3597-89 SEC 7.7

REV. 002
 REV. DATE: 09/30/18
 ISO 9001:2015 • ISO/IEC 17025:2017

Jacobs & Thompson cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of the information or the safety and suitability of our products, either alone or in combination with other products. Unless otherwise agreed in writing, we sell the products without warranty and users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purpose.

Head Office: 89 Kenhar Drive,
 Ontario M9L 2R3
 Tel: (416) 749-0600
 info@foamparts.com
 FoamParts.com