

**Technical Data Sheet**

**Adhesives | Acrylic Adhesives (PSA) | ZA**

**Type:**

Nonwoven fabric supported, low VOC acrylic double sided tape.

**Applications & Features:**

Good adhesion to polyolefin plastics and polyurethane foams. Good conformability to curved surfaces when used as foam adhesive. High heat resistance and durability. Thicker liner provides superior die cutting properties.

**Typical Adhesion Properties:**

<b><u>Properties</u></b>	<b><u>Results</u></b>	<b><u>Test Methods</u></b>
Thickness	130 µm	
Adhesion / SS	21.8 N/25mm	JIS Z0237
Adhesion / ABS	16.6 N/25mm	JIS Z0237
Adhesion / PP	13.8 N/25mm	JIS Z0237
Adhesion / PE	7.4 N/25mm	JIS Z0237
Holding performance 40°C	1.0 mm	JIS Z0237

REV. NO.: 003  
REV. DATE: 09/30/18

Jacobs & Thompson cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of the information or the safety and suitability of our products, either alone or in combination with other products. Unless otherwise agreed in writing, we sell the products without warranty and users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purpose.

Head Office: 89 Kenhar Drive,  
Ontario M9L 2R3  
Tel: (416) 749-0600  
info@foamparts.com  
FoamParts.com